

WRAPTOR® PLUS
MATERIAL SAFETY DATA SHEET

Section 1: Product Identification

Name: Wraptor® Plus
Description: Micro Perforated White Woven Poly w/ Foil Facing
Manufacturer/Distribution: Insulation Solutions, Inc.
Address: 401 Truck Haven Rd.
East Peoria, IL 61611
Toll Free: 866-698-6562
Phone: 309-698-0062
Fax: 309-698-0065
Email: info@insulationsolutions.com

Section 2: Hazardous Ingredients

This product is not considered to be hazardous, and is not classified as a controlled product. It is comprised primarily of polyethylene and aluminum foil, which are considered to be non-hazardous.

Section 3: Physical Data

Boiling Point: Not Applicable
Temperature Range: -50°F to 180°F / -46°C to 82°C
Appearance: Flexible Sheet Material
Odor: None

Section 4: Fire and Explosion Data

Flame Spread: 15 (NFPA Class A, UBC Class 1) (ASTM E-84-03)
Smoke Development: 40 (NFPA Class A, UBC Class 1) (ASTM E-84-03)
Extinguishing Media: CO₂, Dry Chemical, Water or Foam
Usual Fire Hazardous: Polyethylene and aluminum foil are not highly flammable, but in contact with flame they will melt and burn.

Section 5: Reactivity Data

Stability: Product is stable and inert to most chemicals. None cause a violent reaction.
Incompatibility: Check with manufacturer prior to using as a containment or barrier for chemicals other than water.

Section 6: Health Hazard Data

Inhalation: None
Eyes and skin: None
Ingestion: Product should not be eaten or kept in contact with food.

Section 7: Special Precaution & Handling Information

Generally Wraptor® Plus requires no special precautions when handling. However, the material may become slippery when wet, and caution should be taken when used in applications where the product will be walked on.

Note: The information contained in this sheet is disclosed in good faith and is provided to the best knowledge of Insulation Solutions, Inc. It is not a warranty and Insulation Solutions, Inc. assumes no responsibility for damages incurred from the use or inability to use this product.